查询10WQ045FN供应商

Bulletin PD-20530 rev. F 03/03

International
IOR Rectifier

10WQ045FN

SCHOTTKY RECTIFIER

10 Amp

D-Pak (TO-252AA)

Major Ratings and Characteristics

Characteristics	10WQ045FN	Units
$I_{F(AV)}$ Rectangular waveform	10	A
V_{RRM}	45	V
I_{FSM} @ tp = 5 µs sine	400	A
V_F @10Apk, T_J=125°C	0.53	V
T_J range	-40 to 175	°C

Description/ Features

The 10WQ045FN surface mount Schottky rectifier has been designed for applications requiring low forward drop and small foot prints on PC board. Typical applications are in disk drives, switching power supplies, converters, free-wheeling diodes, battery charging, and reverse battery protection.

- Popular D-PAK outline
- Small foot print, surface moutable
- Low forward voltage drop
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability



Conform to JEDEC outline D-Pak (Similar to TO-252AA)
Dimensions in millimeters and (inches)

Voltage Ratings

Part number	10WQ045FN
V_R Max. DC Reverse Voltage (V)	45
V_{RWM} Max. Working Peak Reverse Voltage (V)	

Absolute Maximum Ratings

Parameters	10WQ...	Units	Conditions	
$I_{F(AV)}$ Max. Average Forward Current * See Fig. 5	10	A	50% duty cycle @ T_C = 157°C, rectangular wave form	
I_{FSM} Max. Peak One Cycle Non-Repet. Surge Current * See Fig. 7	400	A	5µs Sine or 3µs Rect. pulse	Following any rated load condition and with rated V_{RRM} applied
	75		10ms Sine or 6ms Rect. pulse	
E_{AS} Non-Repetitive Avalanche Energy	20	mJ	T_J = 25 °C, I_{AS} = 3.0 Amps, L = 4.40 mH	
I_{AR} Repetitive Avalanche Current	3.0	A	Current decaying linearly to zero in 1 µsec Frequency limited by T_J max. V_A = 1.5 x V_R typical	

Electrical Specifications

Parameters	10WQ...	Units	Conditions	
V_{FM} Max. Forward Voltage Drop * See Fig. 1 (1)	0.630	V	@ 10A	T_J = 25 °C
	0.800	V	@ 20A	
	0.530	V	@ 10A	T_J = 125 °C
	0.710	V	@ 20A	
I_{RM} Max. Reverse Leakage Current * See Fig. 2 (1)	1	mA	T_J = 25 °C	V_R = rated V_R
	15	mA	T_J = 125 °C	
$V_{F(TO)}$ Threshold Voltage	0.255	V	T_J = T_J max.	
r_t Forward Slope Resistance	22	mΩ		
C_T Typical Junction Capacitance	760	pF	V_R = 5V_{DC} (test signal range 100Khz to 1Mhz) 25 °C	
L_S Typical Series Inductance	5.0	nH	Measured lead to lead 5mm from package body	

(1) Pulse Width < 300µs, Duty Cycle < 2%

Thermal-Mechanical Specifications

Parameters	10WQ...	Units	Conditions
T_J Max. Junction Temp. Range (*)	- 40 to 175	°C	
T_{stg} Max. Storage Temperature Range	- 40 to 175	°C	
R_{thJC} Max. Thermal Resistance Junction to Case	2.0	°C/W	DC operation * See Fig. 4
R_{thJA} Max. Thermal Resistance Junction to Ambient	50	°C/W	
wt Approximate Weight	0.3 (0.01)	g (oz.)	
Case Style	D - PAK		Similar to TO-252AA

(*) $\frac{dPtot}{dTj} < \frac{1}{Rth(j\text{-}a)}$ thermal runaway condition for a diode on its own heatsink



Fig. 1 - Maximum Forward Voltage Drop Characteristics



Fig. 2 - Typical Values of Reverse Current Vs. Reverse Voltage



Fig. 3 - Typical Junction Capacitance Vs. Reverse Voltage



Fig. 4 - Maximum Thermal Impedance Z_{thJC} Characteristics



Fig. 5 - Maximum Allowable Case Temperature Vs. Average Forward Current



Fig. 6 - Forward Power Loss Characteristics



Fig. 7 - Maximum Non-Repetitive Surge Current

(2) Formula used: $T_C = T_J - (Pd + Pd_{REV}) \times R_{thJC}$;
Pd = Forward Power Loss = $I_{F(AV)} \times V_{FM} @ (I_{F(AV)} / D)$ (see Fig. 6);
Pd_{REV} = Inverse Power Loss = $V_{R1} \times I_R (1 - D)$; $I_R @ V_{R1}$ = 80% rated V_R

Marking Information

EXAMPLE: THIS IS AN 10WQ045FN



Tape & Reel Information





TO-252AA Tape & Reel

When ordering, indicate the part number, part orientation, and the quantity. Quantities are in multiples of 2,000 pieces per reel for TR and multiples of 3,000 pieces per reel for both TRL and TRR.

Data and specifications subject to change without notice.
This product has been designed and qualified for Industrial Level.
Qualification Standards can be found on IR's Web site.

International
IOR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7309
Visit us at www.irf.com for sales contact information. 03/03